

D400
C250

ABU DHABI MUNICIPALITY

MUNICIPALIZZATE



LUOGO DI INSTALLAZIONE
PLACE OF INSTALLATION



CERTIFICAZIONE
CERTIFICATION



CARATTERISTICHE
CHARACTERISTICS



	Codice Code	Telaio Frame cm	Luce netta Net opening cm	Altezza Height cm	Peso Weight kg
	CHDS70-85	90X75	75X60	10	88
	CHDS70-100	105X75	90X60	10	111
	BOCCA KERB5340	54,6X48	53,2x40,5	20,5	63
	CH KERB1 C250	87,3x80,6	66x61	8	92
	GH KERB600		60		17
	GH KERB700		70		19
	CHK-T75-DM	76X76	60	10	67
	T75-90-DM	109X90	90X75	10	157
	GOLFO 60D	76x76	60x60	10	81

ACCESSORI/ACCESSORIES



Chiave di sollevamento 06/ Lifting Key 06

Chiusino in ghisa sferoidale EN-GJS-500-7 a norme EN 1563:2018 con resistenza a rottura superiore a 400 kN (40 t) e 250 kN (25 t), conforme alla classe di carico D400 e C250 prevista dalla norma EN 124:2015

**REALIZZATO PER AZIENDE MUNICIPALIZZATE E
CONSORZI SU PROPRIE SPECIFICHE.**

Inspection manhole cover in ductile iron EN-GJS-500-7 conforming to norm EN 1563:2018 with load bearing capacity over 400 kN (40 tons) and 250 kN (25 tons), conforming to the load class D400 and C250 as set out by norm EN 124:2015

**IT IS REALIZED FOR MUNICIPALITIES AND CONSORTIUMS
ACCORDING TO THEIR SPECIFIC REQUESTS.**

