

CHC70TREV



ASI 2



CHTREV140



LUOGO DI INSTALLAZIONE
PLACE OF INSTALLATION



CERTIFICAZIONE
CERTIFICATION



CARATTERISTICHE
CHARACTERISTICS



Codice Code	Classe Class	Telaio Frame cm	Luce netta Net opening cm	Coperchi Covers cm	Altezza Height cm	Peso Weight kg
CHC70TREV	C250	70x70	60x60	1+1 Ø30	5,5	57
CHTREV140	C250	133x70	124x60	2+2 Ø30	5,5	114
CHC60_INSP	C250	59x59	50x50	1+1 Ø25	5,5	47
CHC90_INSP	C250	90x90	80x80	2+2 Ø30	4,5	90
CHC8767	C250	87x67	74x57	2+2 Ø30	4,6	70
ASI 1	C250	76x61	58x37,4	1+1 Ø30	7	51
ASI 2	C250	74,7x91,4	58x77,7	2+2 Ø30	7	89
ASI 3	C250	74,7x131,6	58x118	3+3 Ø30	8	160
ASI 4	C250	74,7x172	58x158,5	4+4 Ø30	8	215
ASI 5	C250	74,7x212,5	58x199	5+5 Ø30	8	260
ASI 6	C250	74,7x253	58x239	6+6 Ø30	8	310
ASI 7	C250	74,7x293	58x279,4	7+7 Ø30	8	364
CHC50_HERA	C250	49x49	39x39	1	10	28
CHC60_HERA	C250	59x59	50x50	1	10	40
CHB50_HERA	B125	49x49	40x40	1	4	18
CHB60_HERA	B125	59x59	50x50	1	4	26

ACCESSORI/ACCESSORIES



Chiave di sollevamento 06/ Lifting Key 06

Chiusino in ghisa sferoidale EN-GJS-500-7 a norme EN 1563:2018 con resistenza a rottura superiore a 250 kN (25 t), conforme alla classe di carico C250 prevista dalla norma EN 124:2015

REALIZZATO PER AZIENDE MUNICIPALIZZATE
E CONSORZI SU PROPRIE
SPECIFICHE.

Inspection manhole cover in ductile iron EN-GJS-500-7 conforming to norm EN 1563:2018 with load bearing capacity over 250 kN (25 tons), conforming to the load class C250 as set out by norm EN 124:2015

IT IS REALIZED FOR MUNICIPALITIES AND CONSORTIUMS
ACCORDING TO THEIR SPECIFIC REQUESTS.

