

LUOGO DI INSTALLAZIONE
PLACE OF INSTALLATIONCERTIFICAZIONE
CERTIFICATIONCARATTERISTICHE
CHARACTERISTICS

Codice Code		Telaio Frame cm	Luce netta Net opening cm	Altezza Height cm	Sup. deflusso Flow surface dm ²	Peso Weight kg
GHD40	■	42x42	30x30	7,5	6	22
 GHD50 (SIFONABILE)		49x49	38x38	8	10,6	26,5
GHD55_65	■	55x65	45x55	10	18,2	42
 GHD60	■	60x60	48x48	10	13,2	40
 GHD70	■	71x71	59x59	10	24,3	58
GHD70-45°	■	70x70	60x60	10	17,7	70
 GHD80	■	80x80	70x70	10	32,5	70
GHD90	■	92x92	79x79	10	33	95
GHD110	■	112x112	100x100	10	65,8	192
GHD130_80	■	85x130	70x120	10	53,4	156

ACCESSORI/ACCESSORIES

Chiave esagonale /Hexagonal Key

Viti in acciaio diam. 10 /Screws in stainless steel diam. 10

SIFONE SU RICHIESTA-SIPHON ON REQUEST

Caditoia sifonata in ghisa sferoidale EN-GJS-500-7 conforme alla norma EN 1563:2018 con resistenza a rottura superiore 400 KN (40 t) conforme alle classi di carico D400 prevista dalla norma EN 124:2015

TELAIO

Di forma quadrata, alto e rinforzato, assicura una posa stabile e maggiore sicurezza nel traffico. All'esterno presenta un bordo sagomato per ottimizzare la tenuta della malta cementizia.

All'interno presenta un bordo per l'alloggio del sifone.

GRIGLIA

Di forma quadrata piana, con feritoie a rettangoli paralleli, può essere installata nel telaio con le feritoie orientate perpendicolarmente al senso di circolazione, qualunque sia il posizionamento del telaio, onde garantire la sicurezza dei ciclisti, inoltre può essere bloccato con viti in acciaio inox.

SIFONE

Realizzato in ghisa sferoidale EN-GJS-500-7, composto da due tronchi di piramide a base quadrata uniti tra loro da viteria, trattiene i cattivi odori, protegge le fognature dall'ingresso di foglie, sassi e dall'intrusione di ratti.

Self-cleaning and siphoned in ductile iron EN-GJS-500-7 conforming to the norm EN 1563:2018, with load bearing capacity over 400 KN (40 t) conforming with the load classes D400 as set out by norm EN 124:2015

FRAME

It is square in shape with a tall reinforced border, which guarantees a stable setting and greater safety in traffic. The external edge is flanged to optimise its hold in the cement. There is also an inside border which holds the siphon.

GRATING

It comes flat and square in shape, with parallel rectangular slots. It can be installed in the frame with the slots directed perpendicularly to the direction of traffic, no matter the direction of the frame, in order to guarantee the safety of cyclists. Furthermore, it can be blocked with stainless steel screws.

SIPHON

It is made in spheroidal cast iron EN-GJS-500-7, composed of two truncated pyramid with a square base screwed together. It keeps inside bad smells and protects the drains against the introduction of leaves, stones and the intrusion of rats.

